

MODEL	SVC SERİSİ								
	SVC-900WN	SVC-1100WN	SVC-1300WN	SVC-1500WN	SVC-1700WN	SVC-1900WN	SVC-2100WN	SVC-2300WN	SVC-2500WN
Type / Tip	Teleskopik Tip / Telescopic Type								
I.M.M Range Enjeksiyon Aralığı (TON)	160-280	320-450	450-600	600-800	800-1000	1000-1400	1400-1800	1800	2500
Vertical Stroke (mm) Dikey Strok (mm)	900	1100	1300	1500	1700	1900	2100	2300	2500
Crosswise Stroke (mm) Kalıp İçi Strok (mm)	450	630	750	960	960	1200	1200	1550	1550
Transverse Stroke (mm) Yatay Strok (mm)	1450	1680	2000	2400	2400	2860	2860	3360	3360
Max Load (kg) Taşıma Kapasitesi (kg)	5	5	7	25	25	30	35	40	75
Min. Take Out Time (s) Min. Parça Alma Süresi (s)	1.5	2.5	3	4	4.5	5	5.5	6	8
Cycle Time (s) Çevrim Süresi (s)	8	9	10	12	15	18	20	23	25
Drive System Sürüşü Sistemi	X,Y,Z AC SERVO								
Weight (kg) Ağırlık (kg)	210	210	400	550	600	700	750	900	1000